

# 140 AG series

x140x25mm



## General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

## Major Characteristic Parameters

Model	*Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dBA	g
AGE14025_12L	B S	12	7.0~13.2	0.16	1200	1.78	63.0	1.2	0.05	25.0	164
AGE14025_24L	B S	24	14.0~26.4	0.12	1200	1.78	63.0	1.2	0.05	25.0	164
AGE14025_12M	B S	12	7.0~13.2	0.32	1800	2.51	88.6	2.3	0.09	33.0	164
AGE14025_24M	B S	24	14.0~26.4	0.26	1800	2.51	88.6	2.3	0.09	33.0	164
AGE14025_12H	B S	12	7.0~13.2	0.38	2000	2.78	98.4	2.8	0.11	38.0	164

\*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

