

80 AG series

mmx80mmx25mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40°C to +75°C
- Operating temperature : -10°C to +70°C

Major Characteristic Parameters

| Model | *Bearing System | Rated Voltage | Operating Voltage Range | Rated Current | Rated Speed | Maximum Air Flow | | Maximum Static Pressure | | Sound Level | Weight |
|--------------|-----------------|---------------|-------------------------|---------------|-------------|---------------------|------|-------------------------|---------------------|-------------|--------|
| Part NO. | B / S / F | V | V | A | RPM | m ³ /min | CFM | mm-H ₂ O | In-H ₂ O | dBA | g |
| AGF08025_12U | B | 12 | 7.0~13.2 | 0.70 | 5000 | 1.72 | 60.8 | 10.3 | 0.40 | 46.0 | ?? |
| AGF08025_24U | B | 24 | 14.0~26.4 | 0.60 | 5000 | 1.72 | 60.8 | 10.3 | 0.40 | 46.0 | ?? |
| AGF08025_12S | B | 12 | 7.0~13.2 | 0.65 | 6000 | 2.07 | 73.0 | 14.8 | 0.58 | 51.0 | ?? |

*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

