

97 BG series

x97x33mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

Model	Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
BGE09733_12L	B S	12	7.0~13.2	0.21	2200	0.46	16.33	6.15	0.24	43	150
BGE09733_24L	B S	24	14.0~26.4	0.14	2200	0.46	16.33	6.15	0.24	43	150
BGE09733_12M	B S	12	7.0~13.2	0.32	2700	0.57	20.10	10.29	0.40	45	150
BGE09733_24M	B	24	14.0~26.4	0.18	2700	0.57	20.10	10.29	0.40	45	150
BGE09733_12H	B S	12	7.0~13.2	0.60	3600	0.62	28.83	22.04	1.14	52	150
BGE09733_24H	B	24	14.0~26.4	0.32	3600	0.62	28.83	22.04	1.14	52	150

*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

