

□ 120 cooling fan ×120×25mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP120B12L-25DL	B / S	12	7.0~13.2	0.36	4.32	2500	2.6	91.9	5.5	0.22	37.0
SP120B24L-25DL	B / S	24	14.0~26.4	0.25	6.00	2500	2.6	91.9	5.5	0.22	37.0
SP120B12M-25DL	B / S	12	7.0~13.2	0.53	6.36	2800	2.92	103	6.9	0.27	40.0
SP120B24M-25DL	B / S	24	14.0~26.4	0.32	7.68	2800	2.92	103	6.9	0.27	40.0
SP120B12H-25DL	B / S	12	7.0~13.2	0.64	7.68	3100	3.23	114	8.5	0.33	43.0
SP120B24H-25DL	B / S	24	14.0~26.4	0.38	9.12	3100	3.23	114	8.5	0.33	43.0
SP120B12U-25DL	B / S	12	7.0~13.2	0.96	11.52	3400	3.54	125.1	10.2	0.40	45.0
SP120B24U-25DL	B / S	24	14.0~26.4	0.60	14.40	3400	3.54	125.1	10.2	0.40	45.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

