

□ 200 cooling fan ×200×60mm



■ General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller: Al die-casting & Plastic
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP200B24L-60DL	B	24.00	14.0~26.4	0.70	16.80	2000	12.04	425.00	46.40	1.82	46.50
SP200B48L-60DL	B	48.00	28.0~56.0	0.40	19.20	2000	12.04	425.00	46.40	1.82	46.50
SP200B24M-60DL	B	24.00	14.0~26.4	1.00	24.00	2200	13.23	467.00	51.50	2.02	55.80
SP200B48M-60DL	B	48.00	28.0~56.0	0.60	28.80	2200	13.23	467.00	51.50	2.02	55.80
SP200B24H-60DL	B	24.00	14.0~26.4	1.50	36.00	2500	15.04	531.00	58.20	2.29	67.00
SP200B48H-60DL	B	48.00	28.0~56.0	0.80	38.40	2500	15.04	531.00	58.20	2.29	67.00
SP200B24U-60DL	B	24.00	14.0~26.4	2.00	48.00	2800	16.86	595.00	65.00	2.55	74.40
SP200B48U-60DL	B	48.00	28.0~56.0	1.10	52.80	2800	16.86	595.00	65.00	2.55	74.40

*Bearing system B: Two Ball Bearing

