

40 cooling fan

×40×15mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP40B05L-15DL	B/S	5	4.5~5.5	0.12	0.60	4000	0.16	5.80	3.35	0.13	18.9
SP40B12L-15DL	B/S	12	7.0~13.2	0.05	0.60	4000	0.16	5.80	3.35	0.13	18.9
SP40B24L-15DL	B/S	24	14.0~24.6	0.04	0.96	4000	0.16	5.80	3.35	0.13	18.9
SP40B05M-15DL	B/S	5	4.5~5.5	0.21	1.05	6000	0.23	8.13	5.12	0.20	25.3
SP40B12M-15DL	B/S	12	7.0~13.2	0.10	1.20	6000	0.23	8.13	5.12	0.20	25.3
SP40B24M-15DL	B/S	24	14.0~24.6	0.08	1.92	6000	0.23	8.13	5.12	0.20	25.3
SP40B12H-15DL	B/S	12	7.0~13.2	0.14	1.68	8000	0.32	11.36	9.02	0.35	32.6
SP40B24H-15DL	B/S	24	14.0~24.6	0.10	2.40	8000	0.32	11.36	9.02	0.35	32.6
SP40B12U-15DL	B/S	12	7.0~13.2	0.19	2.28	10000	0.38	13.60	12.30	0.48	39.6
SP40B24U-15DL	B/S	24	14.0~24.6	0.12	2.88	10000	0.38	13.60	12.30	0.48	39.6

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

