

60 cooling fan ×60×15mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP60B12L-15DL	B / S	12	7.0~13.2	0.06	0.72	3000	0.43	15.0	2.30	0.09	24.0
SP60B12M-15DL	B / S	12	7.0~13.2	0.08	0.96	3500	0.54	19.0	3.50	0.14	29.0
SP60B12H-15DL	B / S	12	7.0~13.2	0.10	1.20	4000	0.62	21.7	4.10	0.16	32.0
SP60B24H-15DL	B / S	24	14.0~26.4	0.08	1.92	4000	0.62	21.7	4.10	0.16	32.0
SP60B12U-15DL	B / S	12	7.0~13.2	0.12	1.44	4500	0.65	23.1	4.60	0.18	35.0
SP60B24U-15DL	B / S	24	14.0~26.4	0.10	2.40	4500	0.65	23.1	4.60	0.18	35.0
SP60B12HU-15DL	B / S	12	7.0~13.2	0.14	1.68	5000	0.75	26.5	5.70	0.23	37.0
SP60B24HU-15DL	B / S	24	14.0~26.4	0.11	2.64	5000	0.75	26.5	5.70	0.23	37.0

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

