

□ 60 cooling fan ×60×25mm



■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP60B12L-25DL	B / S	12	7.0~13.2	0.10	1.20	3100	0.4	14.1	2.5	0.10	26.0
SP60B24L-25DL	B / S	24	14.0~26.4	0.06	1.44	3100	0.4	14.1	2.5	0.10	26.0
SP60B48L-25DL	B / S	48	28.0~56.0	0.05	2.40	3100	0.4	14.1	2.5	0.10	26.0
SP60B12M-25DL	B / S	12	7.0~13.2	0.12	1.44	3600	0.52	18.5	3.6	0.14	31.0
SP60B24M-25DL	B / S	24	14.0~26.4	0.08	1.92	3600	0.52	18.5	3.6	0.14	31.0
SP60B48M-25DL	B / S	48	28.0~56.0	0.06	2.88	3600	0.52	18.5	3.6	0.14	31.0
SP60B12H-25DL	B / S	12	7.0~13.2	0.16	1.92	4250	0.61	21.5	4.8	0.19	34.0
SP60B24H-25DL	B / S	24	14.0~26.4	0.11	2.64	4250	0.61	21.5	4.8	0.19	34.0
SP60B48H-25DL	B / S	48	28.0~56.0	0.07	3.36	4250	0.61	21.5	4.8	0.19	34.0
SP60B12U-25DL	B / S	12	7.0~13.2	0.35	4.20	5000	0.73	25.6	6.5	0.26	40.0
SP60B24U-25DL	B / S	24	14.0~26.4	0.20	4.80	5000	0.73	25.6	6.5	0.26	40.0
SP60B48U-25DL	B / S	48	28.0~56.0	0.12	5.76	5000	0.73	25.6	6.5	0.26	40.0
SP60B12HU-25DL	B / S	12	7.0~13.2	0.36	4.32	6800	0.99	34.8	13.0	0.51	46.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

