

□ 60 cooling fan ×60×38mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP60B12L-38DL	B / S	12	7.0~13.2	0.60	7.20	8000	1.22	43.1	22.9	0.90	51.0
SP60B24L-38DL	B / S	24	14.0~26.4	0.23	5.52	8000	1.22	43.1	22.9	0.90	51.0
SP60B48L-38DL	B / S	48	28.0~56.0	0.18	8.64	8000	1.22	43.1	22.9	0.90	51.0
SP60B12M-38DL	B / S	12	7.0~13.2	0.90	10.80	9000	1.41	50.0	30.0	1.18	53.5
SP60B24M-38DL	B / S	24	14.0~26.4	0.27	6.48	9000	1.41	50.0	30.0	1.18	53.5
SP60B48M-38DL	B / S	48	28.0~56.0	0.20	9.60	9000	1.41	50.0	30.0	1.18	53.5
SP60B12H-38DL	B / S	12	7.0~13.2	1.28	15.36	10000	1.52	55.2	35.8	1.41	57.0
SP60B24H-38DL	B / S	24	14.0~26.4	0.38	9.12	10000	1.52	55.2	35.8	1.41	57.0
SP60B48H-38DL	B / S	48	28.0~56.0	0.22	10.56	10000	1.52	55.2	35.8	1.41	57.0
SP60B12U-38DL	B / S	12	7.0~13.2	1.80	21.60	12000	1.90	67.3	52.6	2.07	61.8
SP60B24U-38DL	B / S	24	14.0~26.4	0.50	12.00	12000	1.90	67.3	52.6	2.07	61.8
SP60B48U-38DL	B / S	48	28.0~56.0	0.25	12.00	12000	1.90	67.3	52.6	2.07	61.8

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

