

70 cooling fan ×70×15mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP70B12L-15DL	B / S	12	7.0~13.2	0.10	1.20	2800	0.60	21.1	2.30	0.09	27.0
SP70B24L-15DL	B / S	24	14.0~26.4	0.05	1.20	2800	0.60	21.1	2.30	0.09	27.0
SP70B12M-15DL	B / S	12	7.0~13.2	0.12	1.44	3300	0.73	25.7	3.30	0.13	31.0
SP70B24M-15DL	B / S	24	14.0~26.4	0.07	1.68	3300	0.73	25.7	3.30	0.13	31.0
SP70B12H-15DL	B / S	12	7.0~13.2	0.17	2.04	3800	0.84	29.6	4.30	0.17	35.0
SP70B24H-15DL	B / S	24	14.0~26.4	0.10	2.40	3800	0.84	29.6	4.30	0.17	35.0
SP70B12U-15DL	B / S	12	7.0~13.2	0.25	3.00	4300	0.95	33.5	5.50	0.22	39.0
SP70B24U-15DL	B / S	24	14.0~26.4	0.13	3.12	4300	0.95	33.5	5.50	0.22	39.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

