

## □ 70 cooling fan × 70 × 20mm



### ■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### ■ Major Characteristic Parameters

| 品牌            | 轴承    | 电压 | 启动电压      | 电流   | 功率   | 转速   | 风量     | 静压    | 噪音                  |                     |      |
|---------------|-------|----|-----------|------|------|------|--------|-------|---------------------|---------------------|------|
| 型号            | B/S   | V  | V         | A    | W    | RPM  | m3/min | CFM   | mm-H <sub>2</sub> O | In-H <sub>2</sub> O | dba  |
| SP70B12L-20DL | B / S | 12 | 7.0~13.2  | 0.11 | 1.32 | 3200 | 0.83   | 29.16 | 2.99                | 0.12                | 32.0 |
| SP70B24L-20DL | B / S | 24 | 14.0~26.4 | 0.06 | 1.44 | 3200 | 0.83   | 29.16 | 2.99                | 0.12                | 32.0 |
| SP70B12M-20DL | B / S | 12 | 7.0~13.2  | 0.18 | 2.16 | 3800 | 1.00   | 35.42 | 4.30                | 0.17                | 36.5 |
| SP70B24M-20DL | B / S | 24 | 14.0~26.4 | 0.09 | 2.16 | 3800 | 1.00   | 35.42 | 4.30                | 0.17                | 36.5 |
| SP70B12H-20DL | B / S | 12 | 7.0~13.2  | 0.25 | 3.00 | 4400 | 1.15   | 40.43 | 5.64                | 0.22                | 40.5 |
| SP70B24H-20DL | B / S | 24 | 14.0~26.4 | 0.13 | 3.12 | 4400 | 1.15   | 40.43 | 5.64                | 0.22                | 40.5 |
| SP70B12U-20DL | B / S | 12 | 7.0~13.2  | 0.35 | 4.20 | 5000 | 1.33   | 46.86 | 7.24                | 0.29                | 44.3 |
| SP70B24U-20DL | B / S | 24 | 14.0~26.4 | 0.18 | 4.32 | 5000 | 1.33   | 46.86 | 7.24                | 0.29                | 44.3 |

\* Bearing system B: Two Ball Bearing S: Sleeve Bearing

