

## 70 cooling fan × 70 × 25mm



### General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dba
SP70B12L-25DL	B / S	12	7.0~13.2	0.07	0.84	3000	0.85	30.0	3.9	0.15	27.0
SP70B24L-25DL	B / S	24	14.0~26.4	0.05	1.20	3000	0.85	30.0	3.9	0.15	27.0
SP70B48L-25DL	B / S	48	28.0~56.0	0.04	1.92	3000	0.85	30.0	3.9	0.15	27.0
SP70B12M-25DL	B / S	12	7.0~13.2	0.09	1.08	3600	1.02	35.6	5.5	0.22	32.0
SP70B24M-25DL	B / S	24	14.0~26.4	0.06	1.44	3600	1.02	35.6	5.5	0.22	32.0
SP70B48M-25DL	B / S	48	28.0~56.0	0.05	2.40	3600	1.02	35.6	5.5	0.22	32.0
SP70B12H-25DL	B / S	12	7.0~13.2	0.13	1.56	4000	1.13	39.9	6.8	0.27	37.0
SP70B24H-25DL	B / S	24	14.0~26.4	0.08	1.92	4000	1.13	39.9	6.8	0.27	37.0
SP70B48H-25DL	B / S	48	28.0~56.0	0.07	3.36	4000	1.13	39.9	6.8	0.27	37.0
SP70B12U-25DL	B / S	12	7.0~13.2	0.16	1.92	5500	1.55	54.8	12.8	0.50	45.0
SP70B24U-25DL	B / S	24	14.0~26.4	0.35	8.40	5500	1.55	54.8	12.8	0.50	45.0

\* Bearing system B: Two Ball Bearing S: Sleeve Bearing

