

80 cooling fan

×80×15mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

| 品牌 | 轴承 | 电压 | 启动电压 | 电流 | 功率 | 转速 | 风量 | 静压 | 噪音 | | |
|----------------|-------|----|-----------|------|------|------|---------------------|------|---------------------|---------------------|------|
| 型号 | B/S | V | V | A | W | RPM | m ³ /min | CFM | mm-H ₂ O | In-H ₂ O | dba |
| SP80B12L-15DL | B / S | 12 | 7.0~13.2 | 0.06 | 0.72 | 2400 | 0.65 | 23.1 | 1.5 | 0.06 | 28.0 |
| SP80B24L-15DL | B / S | 24 | 14.0~26.4 | 0.04 | 0.96 | 2400 | 0.65 | 23.1 | 1.5 | 0.06 | 28.0 |
| SP80B12M-15DL | B / S | 12 | 7.0~13.2 | 0.08 | 0.96 | 2700 | 0.82 | 28.9 | 2.4 | 0.09 | 31.0 |
| SP80B24M-15DL | B / S | 24 | 14.0~26.4 | 0.06 | 1.44 | 2700 | 0.82 | 28.9 | 2.4 | 0.09 | 31.0 |
| SP80B12H-15DL | B / S | 12 | 7.0~13.2 | 0.11 | 1.32 | 3100 | 0.94 | 33.1 | 2.9 | 0.12 | 34.0 |
| SP80B24H-15DL | B / S | 24 | 14.0~26.4 | 0.08 | 1.92 | 3100 | 0.94 | 33.1 | 2.9 | 0.12 | 34.0 |
| SP80B12U-15DL | B / S | 12 | 7.0~13.2 | 0.15 | 1.80 | 3600 | 1.12 | 39.6 | 4.2 | 0.16 | 39.0 |
| SP80B24U-15DL | B / S | 24 | 14.0~26.4 | 0.09 | 2.16 | 3600 | 1.12 | 39.6 | 4.2 | 0.16 | 39.0 |
| SP80B12HU-15DL | B / S | 12 | 7.0~13.2 | 0.30 | 3.60 | 4500 | 1.35 | 47.6 | 5.5 | 0.22 | 43.0 |

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

