

80 cooling fan × 80 × 38mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP80B12J-38DL	B / S	12	7.0~13.2	0.40	4.80	4200	1.65	58.2	10.4	0.41	45.0
SP80B24J-38DL	B / S	24	14.0~26.4	0.25	6.00	4200	1.65	58.2	10.4	0.41	45.0
SP80B48J-38DL	B / S	48	28.0~56.0	0.14	6.72	4200	1.65	58.2	10.4	0.41	45.0
SP80B12L-38DL	B / S	12	7.0~13.2	0.51	6.12	4900	1.96	69.1	14.2	0.56	49.0
SP80B24L-38DL	B / S	24	14.0~26.4	0.41	9.84	4900	1.96	69.1	14.2	0.56	49.0
SP80B48L-38DL	B / S	48	28.0~56.0	0.23	11.04	4900	1.96	69.1	14.2	0.56	49.0
SP80B12M-38DL	B / S	12	7.0~13.2	0.60	7.20	5200	2.23	78.8	19.3	0.76	53.0
SP80B24M-38DL	B / S	24	14.0~26.4	0.55	13.20	5200	2.23	78.8	19.3	0.76	53.0
SP80B48M-38DL	B / S	48	28.0~56.0	0.33	15.84	5200	2.23	78.8	19.3	0.76	53.0
SP80B12H-38DL	B / S	12	7.0~13.2	0.85	10.20	6100	2.40	84.8	22.7	0.89	56.0
SP80B24H-38DL	B / S	24	14.0~26.4	0.78	18.72	6100	2.40	84.8	22.7	0.89	56.0
SP80B48H-38DL	B / S	48	28.0~56.0	0.51	24.48	6100	2.40	84.8	22.7	0.89	56.0
SP80B12U-38DL	B / S	12	7.0~13.2	1.55	18.60	7500	2.99	105.5	34.5	1.36	62.0
SP80B24U-38DL	B / S	24	14.0~26.4	1.17	28.08	7500	2.99	105.5	34.5	1.36	62.0
SP80B48U-38DL	B / S	48	28.0~56.0	0.58	27.84	7500	2.99	105.5	34.5	1.36	62.0
SP80B12HU-38DL	B / S	12	7.0~13.2	2.60	31.20	9000	3.68	130.0	50.9	2.00	65.5
SP80B24HU-38DL	B / S	24	14.0~26.4	1.80	43.20	9000	3.68	130.0	50.9	2.00	65.5
SP80B48HU-38DL	B / S	48	28.0~56.0	0.90	43.20	9000	3.68	130.0	50.9	2.00	65.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

