

□ 92 cooling fan ×92×25mm



■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP92B12L-25DL	B / S	12	7.0~13.2	0.09	1.08	2100	1.11	39.2	2.2	0.09	25.0
SP92B24L-25DL	B / S	24	14.0~26.4	0.06	1.44	2100	1.11	39.2	2.2	0.09	25.0
SP92B48L-25DL	B / S	48	28.0~56.0	0.05	2.40	2100	1.11	39.2	2.2	0.09	25.0
SP92B12M-25DL	B / S	12	7.0~13.2	0.11	1.32	2450	1.27	44.8	2.9	0.11	30.0
SP92B24M-25DL	B / S	24	14.0~26.4	0.08	1.92	2450	1.27	44.8	2.9	0.11	30.0
SP92B48M-25DL	B / S	48	28.0~56.0	0.06	2.88	2450	1.27	44.8	2.9	0.11	30.0
SP92B12H-25DL	B / S	12	7.0~13.2	0.14	1.68	2850	1.48	52.1	3.9	0.16	34.0
SP92B24H-25DL	B / S	24	14.0~26.4	0.13	3.12	2850	1.48	52.1	3.9	0.16	34.0
SP92B48H-25DL	B / S	48	28.0~56.0	0.08	3.84	2850	1.48	52.1	3.9	0.16	34.0
SP92B12U-25DL	B / S	12	7.0~13.2	0.20	2.40	3200	1.65	58.3	4.7	0.18	38.0
SP92B24U-25DL	B / S	24	14.0~26.4	0.15	3.60	3200	1.65	58.3	4.7	0.18	38.0
SP92B48U-25DL	B / S	48	28.0~56.0	0.12	5.76	3200	1.65	58.3	4.7	0.18	38.0
SP92B12HU-25DL	B / S	12	7.0~13.2	0.35	4.20	3800	1.96	69.2	6.6	0.26	45.0
SP92B24HU-25DL	B / S	24	14.0~26.4	0.20	4.80	3800	1.96	69.2	6.6	0.26	45.0
SP92B48HU-25DL	B / S	12	7.0~13.2	0.41	4.92	4200	2.29	81.0	9.2	0.40	49.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

