

120 DC Blower

× 120 × 32mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音
型号	B/S	V	V	A	W	RPM	m ³ /min CFM	mm-H ₂ O In-H ₂ O	dba
SP120B12I-32DL	B/S	12	7.0~13.2	0.38	4.56	2100	0.69 24.2	18.93 0.745	48
SP120B24L-32DL	B/S	24	14.0~26.4	0.20	4.80	2100	0.69 24.2	18.93 0.745	48
SP120B48L-32DL	B/S	48	28.0~56.0	0.10	4.80	2100	0.69 24.2	18.93 0.745	48
SP120B12M-32DL	B/S	12	7.0~13.2	0.66	7.92	2300	0.82 28.67	29.18 1.149	52.4
SP120B24M-32DL	B/S	24	14.0~26.4	0.33	7.92	2300	0.82 28.67	29.18 1.149	52.4
SP120B48M-32DL	B/S	48	28.0~56.0	0.17	8.16	2300	0.82 28.67	29.18 1.149	52.4
SP120B12H-32DL	B/S	12	7.0~13.2	0.88	10.56	2500	0.91 32.13	34.45 1.356	54.7
SP120B24H-32DL	B/S	24	14.0~26.4	0.44	10.56	2500	0.91 32.13	34.45 1.356	54.7
SP120B48H-32DL	B/S	48	28.0~56.0	0.22	10.56	2500	0.91 32.13	34.45 1.356	54.7
SP120B12U-32DL	B/S	12	7.0~13.2	1.55	18.60	2800	1.09 38.63	50.59 1.992	58.5
SP120B24U-32DL	B/S	24	14.0~26.4	0.77	18.48	2800	1.09 38.63	50.59 1.992	58.5
SP120B48U-32DL	B/S	48	28.0~56.0	0.38	18.24	2800	1.09 38.63	50.59 1.992	58.5
SP120B12HU-32DL	B/S	12	7.0~13.2	1.90	22.80	3200	1.29 45.57	73.64 2.9	62.5
SP120B24HU-32DL	B/S	24	14.0~26.4	0.95	22.80	3200	1.29 45.57	73.64 2.9	62.5
SP120B48HU-32DL	B/S	48	28.0~56.0	0.48	23.04	3200	1.29 45.57	73.64 2.9	62.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

