

30 DC Blower

×30×10mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP30B05L-10DL	B / S	5	4.5~5.5	0.06	0.30	5500	0.030	1.06	3.66	0.144	24.0
SP30B12L-10DL	B / S	12	7.0~13.2	0.04	0.48	5500	0.030	1.06	3.66	0.144	24.0
SP30B05M-10DL	B / S	5	4.5~5.5	0.08	0.40	6500	0.035	1.24	5.23	0.206	26.0
SP30B12M-10DL	B / S	12	7.0~13.2	0.05	0.60	6500	0.035	1.24	5.23	0.206	26.0
SP30B05H-10DL	B / S	5	4.5~5.5	0.11	0.55	7500	0.041	1.45	7.24	0.285	29.0
SP30B12H-10DL	B / S	12	7.0~13.2	0.06	0.72	7500	0.041	1.45	7.24	0.285	29.0
SP30B05U-10DL	B / S	5	4.5~5.5	0.15	0.75	8500	0.047	1.66	9.40	0.370	31.0
SP30B12U-10DL	B / S	5	4.5~5.5	0.15	0.75	8500	0.047	1.66	9.40	0.370	31.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

