

40 DC Blower

× 40 × 20mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP40B05L-20DL	B/S	5	4.5~5.5	0.14	0.70	3000	0.06	2.20	3.00	0.11	21.4
SP40B12L-20DL	B/S	12	7.0~13.2	0.07	0.84	4200	0.08	2.90	4.90	0.19	25.5
SP40B05M-20DL	B/S	5	4.5~5.5	0.20	1.00	4200	0.08	2.90	4.90	0.19	25.5
SP40B12M-20DL	B/S	12	7.0~13.2	0.11	1.32	5300	0.09	3.50	6.80	0.26	29.6
SP40B05H-20DL	B/S	5	4.5~5.5	0.26	1.30	5300	0.09	3.50	6.80	0.26	29.6
SP40B12H-20DL	B/S	12	7.0~13.2	0.15	1.80	6000	0.11	4.10	8.50	0.33	34.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

