

# 75 DC Blower

×75×15mm



## General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

## Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dba
SP75B05L-15DL	B/S	5	4.5~5.5	0.16	0.80	2500	1.05	3.72	10.58	0.41	27.0
SP75B12L-15DL	B/S	12	7.0~13.2	0.11	1.32	2500	1.05	3.72	10.58	0.41	27.0
SP75B24L-15DL	B/S	24	14.0~26.4	0.06	1.44	2500	1.05	3.72	10.58	0.41	27.0
SP75B05M-15DL	B/S	5	4.5~5.5	0.24	1.20	3000	0.11	4.04	12.07	0.47	31.0
SP75B12M-15DL	B/S	12	7.0~13.2	0.12	1.44	3000	0.11	4.04	12.07	0.47	31.0
SP75B12H-15DL	B/S	12	7.0~13.2	0.35	4.20	3500	0.13	4.67	15.09	0.59	35.0
SP75B24H-15DL	B/S	24	14.0~26.4	0.18	4.32	3500	0.13	4.67	15.09	0.59	35.0
SP75B24U-15DL	B/S	24	14.0~26.4	0.30	7.20	4000	0.14	4.90	16.03	0.63	42.0

\*Bearing system B: Two Ball Bearing S: Sleeve Bearing

