

97 DC Blower

×97×33mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌 型号	轴承 B/S	电压 V	启动电压 V	电流 A	功率 W	转速 RPM	风量 m3/min	CFM	静压 mm-H2O	In-H2O	噪音 dba
SP97B12L-33DL	B/S	12	7.0~13.2	0.38	4.56	2700	0.69	24.20	18.93	0.75	48.0
SP97B24L-33DL	B/S	24	14.0~26.4	0.19	4.56	2700	0.69	24.20	18.93	0.75	48.0
SP97B48L-33DL	B/S	48	28.0~56.0	0.10	4.80	2700	0.69	24.20	18.93	0.75	48.0
SP97B12M-33DL	B/S	12	7.0~13.2	0.66	7.92	3200	0.82	28.67	29.18	1.15	52.4
SP97B24M-33DL	B/S	24	14.0~26.4	0.33	7.92	3200	0.82	28.67	29.18	1.15	52.4
SP97B48M-33DL	B/S	48	28.0~56.0	0.17	7.92	3200	0.82	28.67	29.18	1.15	52.4
SP97B12H-33DL	B/S	12	7.0~13.2	0.88	10.56	3600	0.91	32.13	34.45	1.36	54.7
SP97B24H-33DL	B/S	24	14.0~26.4	0.44	10.56	3600	0.91	32.13	34.45	1.36	54.7
SP97B48H-33DL	B/S	48	28.0~56.0	0.22	10.56	3600	0.91	32.13	34.45	1.36	54.7
SP97B12U-33DL	B/S	12	7.0~13.2	1.55	18.60	4200	1.09	38.63	50.59	1.99	58.5
SP97B24U-33DL	B/S	24	14.0~26.4	0.78	18.60	4200	1.09	38.63	50.59	1.99	58.5
SP97B48U-33DL	B/S	48	28.0~56.0	0.39	18.60	4200	1.09	38.63	50.59	1.99	58.5
SP97B12HU-33DL	B/S	12	7.0~13.2	1.90	22.80	5000	1.29	45.57	73.64	2.90	62.5
SP97B24HU-33DL	B/S	24	14.0~26.4	0.95	22.80	5000	1.29	45.57	73.64	2.90	62.5
SP97B48HU-33DL	B/S	48	28.0~56.0	0.48	22.80	5000	1.29	45.57	73.64	2.90	62.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

